# **ONSET**

## **HOBO® RG3 Rain Gauge**

### Rainfall data logging system

The HOBO RG3 data logging rain gauge is a self-contained device that includes an integrated data logger with a high-quality tipping-bucket rain gauge. The RG3's logger has a built-in temperature sensor and is on a cable so it can be used in an optional radiation shield for logging air temperature.

Supported Measurements: Rainfall, Temperature

#### **Key Advantages:**

- Aluminum housing and 15.4 cm (6.06 in) collector ring
- Field-proven design
- Logger can be moved into an optional radiation shield for logging air temperature
- Three mounting feet to use on flat, level surfaces
- Side bracket for mast mounting (hose clamps included)
- · Self-emptying for continuous rainfall logging

#### **Minimum System Requirements:**





Software Base Station

#### ▶ For complete information and accessories, please visit: www.onsetcomp.com

| Part numbers          | RG3-M, RG3   |
|-----------------------|--|
|                       |  |
| Memory                | Events only: 16K to 23K events<br>Events and temperature: 25K to 30K data points   |
| Measurement range     | Up to 320 cm (RG3-M), up to 160 in (RG3)   |
| Resolution            | 0.2 mm (RG3-M), 0.01 in (RG3)  |
| Time stamp resolution | 1 second   |
| Maximum Rainfall rate | 12.7 cm (5 in) per hour  |
| Battery life          | 1 year typical, user-replaceable, CR2032   |
|                       | Temperature  |
| Measurement range     | -20° to 70°C (-4° to 158°F)  |
| Accuracy              | ± 0.53°C from 0° to 50°C (± 0.95°F from 32° to 122°F); a solar radiation shield is required for temperature measurements in sunlight |
| Resolution            | 0.14°C at 25°C (0.25°F at 77°F)  |
| Sample rate           | 1 second to 18 hours, user-selectable  |
| Dimensions            | 15.2 cm diameter x 25.7 cm high (6 x 10 in) 1.2 kg (2.5 lbs)   |
| CE compliant          | Yes  |

